

REMARKS

By way of the foregoing amendments to the claims, Claims 1-10 have been amended to delete the multiple dependencies and reference numerals. These changes have been made in accordance with 37 C.F.R. § 1.121 as amended on November 7, 2000. Marked-up versions of Claims 1-10 indicating the changes accompany this Preliminary Amendment.


Early and favorable consideration with respect to this application is respectfully requested.

Should any questions arise in connection with this application, the undersigned respectfully requests that he be contacted at the number indicated below.

Respectfully submitted,

~~BURNS, DOANE, SWECKER & MATHIS, L.L.P.~~

By: _____


Robert S. Swecker
Registration No. 19,885

P. O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Date: April 25, 2001

Attachment to Preliminary Amendment dated April 25, 2001

Marked-up Claims 1-10

1. (Amended) A high-voltage insulation system for electrical insulation of components whose operating temperature is below ambient temperature comprising a coolant [(3)] and a solid material [(2)] having a cured polymer matrix [(21)] and a base fabric [(20)], [characterized in that] wherein the base fabric [(20)] comprises cellulose.

2. (Amended) The high-voltage insulation system as claimed in claim 1, [characterized in that] wherein the coolant [(3)] comprises liquid nitrogen and the components contain high-temperature superconductor material.

3. (Amended) The high-voltage insulation system as claimed in claim 1, [characterized in that] wherein, in order to make the components mechanically robust, the base fabric [(20)] is in the form of pressboards.

4. (Amended) The high-voltage insulation system as claimed in claim 3, [characterized in that] wherein the base fabric comprises a laminate [(6)] having at least two layers [(20, 61)] of pressboards, which are separated by at least one intermediate layer [(62)].

5. (Amended) The high-voltage insulation system as claimed in claim 4, [characterized in that] wherein the intermediate layer [(62)] comprises a fabric composed of cotton, nylon or polyethylene fibers.

Attachment to Preliminary Amendment dated April 25, 2001

Marked-up Claims 1-10

6. (Amended) The high-voltage insulation system as claimed in claim 1 [or 4], [characterized in that] wherein, in order to grade electrical fields, carbon in the form of fibers or fabrics is added to the base fabric [(20)] or to the intermediate layer [(62)].

7. (Amended) The high-voltage insulation system as claimed in claim 1 [or 4], [characterized in that] wherein, for mechanical reinforcement glass fibers in the form of fibers or fabrics are added to the base fabric [(20)] or to the intermediate layer [(62)].

8. (Amended) A method for producing a high-voltage insulation system comprising a coolant [(3)] and a solid material [(2)] having a cured polymer matrix [(21)] and a base fabric [(20)],

[characterized in that] wherein a base fabric [(20)] comprising cellulose is formed in the dry state as a pressboard and is then impregnated with a polymer resin.

9. (Amended) The method as claimed in claim 8, [characterized in that] wherein the pressboard has a thickness d , and a minimum radius of curvature R , and in that the ratio R/d is less than 150.

10. (Amended) The method as claimed in claim 8, [characterized in that] wherein the formed pressboard forms a coil former [(6)] on which at least one winding of a

Attachment to Preliminary Amendment dated April 25, 2001

Marked-up Claims 1-10

superconducting conductor [(1')] is wound, and the coil former [(6)] and the winding [(1')] are then impregnated jointly.